

PANELUXE™ MULTI-END ROVING

Optimal panel clarity performance



PANELUXE™ multi-end roving represents a compelling solution for panels where excellent translucency performance is required.

- ✓ Produced with patented Advantex® corrosion resistant E-CR glass.
- ✓ Based on the process and type of resin system, PANELUXE™ roving can be used as an alternative to HILIGHT® roving.
- ✓ Compatible with unsaturated polyester resins.

FOR TRANSLUCENT AND OPAQUE GLASS-REINFORCED PANELS

Product Benefits



Excellent Processability

- Designed for excellent processing at various line speeds, PANELUXE™ roving features easy unwinding and chopping, flat lay-down, and uniform dispersion with low fuzz and static.
- With high impregnation and wet-through characteristics, the product allows excellent resin flow in translucent applications.



Impressive Aesthetics

- Excellent fiber distribution provides a homogeneous surface aspect with limited fiber prints, resulting in consistent thickness throughout the laminate.
- Absence of white fibers and fiber spring-back along with significant reduction of air entrapment ensures excellent translucency of laminates.



Enhanced Service Life

- Advantex® glass helps fight corrosion, enhancing service life compared to standard E-glass.

Application

PANELUXE™ roving is designed to provide optimal translucency in skylight panels, greenhouses, decorative panels for commercial buildings, and roofs for trucks and industrial buildings.



Technical Characteristics

LINEAR WEIGHT OF ROVING (TEX)	YIELDS (YD/LB)	LOSS ON IGNITION (%) ISO 1887:1995
2400	207	0.65

Availability & Packaging

Each pallet can be packaged in bulk or Creel-Pak™ packaging format. Pallets are stretch-wrapped for load stability and for protection during transport. All individual packages are wrapped with Tack-Pak® packaging to aid package run-out and transfer. More information is available in the Customer Acceptance Standards.

MANUFACTURING REGION	PRODUCT	LAYERS PER PALLET	DOFFS PER LAYER	NUMBER OF ENDS	PALLET NET WEIGHT (KG/LB)
Europe	PANELUXE™ 2400	3	16	48 (BP) and 16	820/1,808

Labeling

Each doff has a self-adhesive identification label showing the product description, net weight and production date. Each pallet has at least two identification labels detailing the product reference, pallet net and gross weights, production date and pallet production code.

Storage

Unless otherwise specified, it is recommended that glass fiber products be stored in a cool, dry area. Recommended long-term storage conditions are temperatures between 10 °C and 35 °C and relative humidity between 35% and 85%. While temporary deviations may occur during storage or transportation, product performance can be confirmed through routine verification testing if exposure outside these conditions has occurred for an extended period. Glass fiber products should remain in their original packaging until the point of use. To help prevent condensation, keep product in its original, unopened packaging and allow it to naturally acclimate to the workshop temperature for at least 24 hours before opening or use. Packaging is not waterproof and should be protected from weather and other sources of moisture. Although fluctuations may occur during transportation, handling, and temporary storage, products should be maintained within the recommended storage ranges after receipt to help preserve product performance. A defined shelf life has not been established for the product when stored under recommended conditions. However, retesting is recommended after two years from the date of manufacture to help ensure optimum performance.

MAKE
MORE
POSSIBLE™

Europe (France)
767 Quai Des Allobroges
Chambery
Rhone-Alpes 73000, France
+33 4 79 75 55 52

This information and data contained herein is offered solely as a guide in the selection of product. We do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The physical and chemical properties of this product represent typical, average values obtained in accordance with stated test methods and are subject to normal manufacturing variations. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10023874. PANELUXE™ Product Data Sheet. October 2026. English. © 2026 OCF - Original Composites & Fiberglass. All Rights Reserved.