

147A-14P

Excellent flow,
accurate dosage




147A-14P chopped fibers are manufactured with Advantex® glass technology from continuous filaments joined into strands, which receive a chemical coating suitable for interaction with a polymeric matrix of PP (polypropylene) and PE (polyethylene).

- ✓ Ease of dispersion and homogenization of filaments in extrusion processes.
- ✓ Excellent flow characteristics in dosing systems.
- ✓ Increase in mechanical properties, as well as in the thermo-distortion temperature of the final composite.


YOUR REINFORCEMENT WITH PRECISE DOSAGE

Product Benefits



Polymer Compatibility

- Adequate interaction with PP and PE polymer matrices.



Processing Consistency

- Supports stable performance in extrusion and dosing systems.



Reliable Strand Integrity

- Excellent strand integrity during handling and processing.



Certified Manufacturing

- Produced under ISO 9001, ISO 14001 and OHSAS 18001 certifications.

Application

147A-14P is designed for application in extrusion and/or injection processes of thermoplastic polymers, aiming to act as reinforcement in polypropylene and polyethylene composites.



Availability & Packaging

PRODUCT NAME	NOMINAL FILAMENT DIAMETER	NOMINAL SOLIDS CONTENT	NOMINAL LENGTH
147A-14P	14 µm	0.7%	4 mm

147A-14P chopped fibers are available in polyethylene Bulk Bags with a total net weight of 1000 kg.

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. Ideal conditions are at a temperature between 15 °C and 35 °C and a relative humidity between 35% and 65%. The glass fiber products must remain in their original packaging material until the point of usage. Still in its original packaging, the product should be stored in the area where it will be used up to 48 hours prior to use, especially during colder seasons, to allow it to reach room temperature and help prevent condensation. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, and retesting is advised after three years from the initial production date to ensure optimum performance.

The wooden pallets used do not permit storage on racks with free gaps. OCF will not be responsible for any damage resulting from stacking more than two pallets or from storing the product on racks without a solid base capable of supporting the respective gross weight. Additional storage details can be found in the Customer Acceptance Standards.

MAKE
MORE
POSSIBLE™

US & Canada
2790 Columbus Road
Building 70
Granville, Ohio, USA 43023
+1 866 2GET GLAS

South America
Av. Brasil, 2567
Rio Claro/SP, Brasil
13500-600
0800 707 3312

This information and data contained herein is offered solely as a guide in the selection of product. We do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The physical and chemical properties of this product represent typical, average values obtained in accordance with stated test methods and are subject to normal manufacturing variations. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10028680. 147A-14P Product Data Sheet. July 2026. English. © 2026 OCF - Original Composites & Fiberglass. All Rights Reserved.