

P207

MULTI-END ROVING

Optimize application
performance



P207 multi-end roving represents a compelling solution for fabricators that want to save time while realizing optimal performance for continuous process spray-up applications.

- ✓

Produced with patented Advantex® corrosion resistant E-CR glass.
- ✓

Compatible with polyester and vinyl ester resin systems.

FOR SPRAY-UP IN LARGE AND VERTICAL PARTS

Product Benefits

- 

Excellent Processing

 - Low fuzz combined with ease of chopping, and roll out, outstanding compatibility for flat lay down, and uniform dispersion saves time.
 - Designed to provide optimal performance for spray-up applications where medium wet-out speed is preferred.
 - Superior processing performances achieved with highly filled resin systems.
- 

Exceptional Performance

 - Great surface quality, excellent conform-ability, doesn't trap air, and low springback.
 - Features Advantex® glass fiber, which combines the electrical (no static) and mechanical properties of traditional E-glass with the acid corrosion resistance of E-CR glass.
 - Ease of use and supreme performance on vertical parts and large or complex molds.

Application

P207 roving can be used in a variety of spray-up applications, including boats, truck caps, vehicle body parts, bath tubs, showers, spas, tanks, and applications with large parts, complex molds, or sharp curvatures.

Technical Characteristics

LINEAR WEIGHT OF ROVING (TEX) (G/KM)	LOSS ON IGNITION (%)	MOISTURE CONTENT (%)
	ISO 1887:1995	ISO 3344:1997
2400 +/- 120	1.10% +/- 0.15	≤ 0.15

Availability & Packaging

PRODUCT	DOFF CHARACTERISTICS			
	DIAMETER (mm)		HEIGHT (mm)	NOMINAL WEIGHT (kg)
	INTERNAL	EXTERNAL		
P207 2400	75	280	260	19

- Each P207 doff is protected by a Tack-Pak® polythene film and identified by an individual label; please do not remove film during use.
- Creel-Pak® and customer-specific packaging may be available upon request.

PRODUCT	DOFF Ø (MM)	PALLET DIMENSIONS LxW (CM)	LAYERS PER PALLET	DOFFS PER LAYER	TOTAL NUMBER OF DOFFS	CREEL-PAK®	PALLETS		MANUFACTURING REGION
						NUMBER OF ENDS	APPROX. HEIGHT (CM)	NET WEIGHT* (KG)	
P207 2400	280	114 x 114	3/4	16	48/64	1 - 2 - 4 - 8 - 16	93/119	912/1216	Europe and North America

Test results will vary by Process and Formulation.

Labeling

Each doff has a self-adhesive identification label, showing the product reference and the production date.

Each pallet has five identification labels detailing the product reference, pallet net and gross weights, production date, and pallet production code.

Storage

Unless otherwise specified, it is recommended that glass fiber products be stored in a cool, dry area. Recommended long-term storage conditions are temperatures between 10°C and 35°C and relative humidity between 35% and 85%. While temporary deviations may occur during storage or transportation, product performance can be confirmed through routine verification testing if exposure outside these conditions has occurred for an extended period. Glass fiber products should remain in their original packaging until the point of use. To help prevent condensation, keep product in its original, unopened packaging and allow it to naturally acclimate to the workshop temperature for at least 24 hours before opening or use. Packaging is not waterproof and should be protected from weather and other sources of moisture. Although fluctuations may occur during transportation, handling, and temporary storage, products should be maintained within the recommended storage ranges after receipt to help preserve product performance. A defined shelf life has not been established for the product when stored under recommended conditions. However, retesting is recommended after two years from the date of manufacture to help ensure optimum performance.

MAKE
MORE
POSSIBLE™

US & Canada
2790 Columbus Road
Building 70
Granville, Ohio, USA 43023
+1 866 2GET GLAS

Europe (France)
767 Quai Des Allobroges
Chambery
Rhône-Alpes 73000, France
+33 4 79 75 55 52

This information and data contained herein is offered solely as a guide in the selection of product. We do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The physical and chemical properties of this product represent typical, average values obtained in accordance with stated test methods and are subject to normal manufacturing variations. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10024127. P207 Product Data Sheet. October 2026. English. © 2026 OCF - Original Composites & Fiberglass. All Rights Reserved.