Original
Composites &
Fiberglass

ME3060
MULTI-END ROVING

Impressive surface aspect

ME3060, a multi-end, choppable roving, represents a compelling solution for the manufacture of stitched fabrics used in industrial applications.

- Produced with patented Advantex® corrosion resistant E-CR glass.
- Compatible with epoxy, polyester and vinyl ester unsaturated resins.

FOR FABRIC WEAVING APPLICATIONS

Product Benefits

Excellent Processability

- Flat wet-out and excellent resin impregnation characteristics.
- Designed for excellent processing at various line speeds, ME3060 features easy unwinding and chopping, flat lay-down, and uniform dispersion with low fuzz and static.

Impressive Aesthetics

- Low Tex with high-fiber distribution provides a homogeneous surface aspect with limited fiber prints and excellent surface finishing.

Enhanced Service Life

- Compared to standard E-glass, Advantex® glass helps with enhanced service life in applications facing corrosion.

Application

ME3060 is designed for the manufacture of stitched fabrics that are used for a variety of industrial applications, tanks and pipes, marine, and certain wind blade applications.

ME3060 | FABRIC WEAVING | OCTOBER 2026

Technical Characteristics

LINEAR WEIGHT OF ROVING (TEX) (G/KM) ISO 1889:1987	YIELD (YD/LB)	NOMINAL LOI (LOSS ON IGNITION) (%)
2400	207	1.25

Availability & Packaging

ME3060 is available in Europe.

Each pallet can be packaged in bulk or Creel-Pak® packaging format. Pallets are stretch wrapped for load stability and for protection during transport. All individual packages are wrapped with Tack-Pak® packaging to aid package run-out and transfer. More information is available in the Customer Acceptance Standards.

MANUFACTURING REGION	TEX	DOFF Ø (MM)	PALLET L x W (CM)	LAYERS PER PALLET	DOFFS PER LAYER	TOTAL NUMBER OF DOFFS	CREEL-PAK® NUMBER OF ENDS	PALLET HEIGHT (CM)	PALLET NET* WEIGHT (KG)
Europe	ME3060	290	90 x 120/ 120 x 120	4	12/16	48/64	12 & 16	120	1032 / 1376

* Add 35 kg to obtain gross weight.

Labeling

Each doff has a self-adhesive identification label showing the product description, net weight, and production date.

Storage

Unless otherwise specified, it is recommended that glass fiber products be stored in a cool, dry area. Recommended long-term storage conditions are temperatures between 10 °C and 35 °C and relative humidity between 35% and 85%. While temporary deviations may occur during storage or transportation, product performance can be confirmed through routine verification testing if exposure outside these conditions has occurred for an extended period. Glass fiber products should remain in their original packaging until the point of use. To help prevent condensation, keep product in its original, unopened packaging and allow it to naturally acclimate to the workshop temperature for at least 24 hours before opening or use. Packaging is not waterproof and should be protected from weather and other sources of moisture. Although fluctuations may occur during transportation, handling, and temporary storage, products should be maintained within the recommended storage ranges after receipt to help preserve product performance. A defined shelf life has not been established for the product when stored under recommended conditions. However, retesting is recommended after two years from the date of manufacture to help ensure optimum performance.

MAKE MORE POSSIBLE™

Europe (France)
767 Quai Des Allobroges
Chambery
Rhone-Alpes 73000, France
+33 4 79 75 55 52

This information and data contained herein is offered solely as a guide in the selection of product. We do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The physical and chemical properties of this product represent typical, average values obtained in accordance with stated test methods and are subject to normal manufacturing variations. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10024328. ME3060 Product Data Sheet. October 2026. English. © 2026 OCF - Original Composites & Fiberglass. All Rights Reserved.